



DMT430H MARINE TRANSMISSION SPECIFICATION			
GEAR RATIO	2.06, 2.44, 2.93, 3.23, 3.4		
TOTAL WEIGHT	APPROX. 694Kg(DRY)		
OIL CAPACITY	APPROX. 11L		
OIL VISCOSITY	SAE # 30		
OIL PRESSURE	1.96 ~ 2.54 MPa	CLUTCH OIL	
DIRECTION OF ROTATION IN FORWARD	INPUT	C.C.W VIEWED FROM THE STERN	
	OUTPUT	C.W VIEWED FROM THE STERN	
OIL CHANGE INTERVAL	THE FIRST 100HOURS OF INITIAL OPERATION		
	AND EVERY 1000HOURS THEREAFTER		
SHIFTING LIMIT	UNDER 50% OF THE RATED ENGINE SPEED		
OIL COOLER	WATER FLOW 90 ~ 120L/m		
	TEMPERATURE OF COOLING WATER		MAX 32°C
OPERATING TORQUE OF SHIFTING LEVER		UNDER 2.94Nm	

REMARK

1.HOUSING : SAE# 1

2.DRIVING RING : SAE 14"

3.COUPLING TYPE

- CENTA Flex Coupling : 77318801

공통공차 TOLERANCE ON				번호 NO.	품 PART NO.	품 PART NAME	개 수 Q'TY	재 MATERIAL	규 SIZE	비 REMARKS
분 수 FRACTIONS				소 수 DECIMALS		각 도 ANGLES				
±				±		±				